

Air Conditioning Compressor Air Leak Detection in Air Conditioner Compressors by using Image Processing Techniques for Industrial Applications

First Author¹, Second Author^{2*}, Third Author³

¹ First Department, First University, Address, City, Country Name

² Second Company Department, Company Address, City, Country Name

³ Third Department, Third University, Address, Country Name

⁴ Current affiliation: Fourth Department, Fourth University, Address, Country Name
*corresponding.author@second.com

Abstract: Ideally, an air conditioner compressor should not have air leakages. However, poor inspection techniques can allow for defects to pass through, which can cause air leakages in compressors. This paper presents a method to detect air leakage of in an air conditioning conditioner compressor using image processing techniques. Quality of air conditioning compressor should not have air leakage. In order to test inspect an air conditioning conditioner compressor for air leakage, air is pumped into a the compressor, which is and then submerged into the a water tank. If air bubbles are observed occurs at the surface of the air conditioning compressor, it implies that air leakage exists, and the that leakage compressor must then be returned for maintenance. In this workstudy, a new method to detect air leakage and search identify the leakage point with high accuracy, speed, and reliability, fast, and precise processes was proposed. In a preprocessing procedure to detect the air bubbles, threshold and median filter techniques have been used. Connected-component labelling technique and blob analysis are is used to detect the air bubbles while blob analysis is searching technique to and analyze the group of the air bubbles in sequential images, respectively. The experiments are tested evaluate with the proposed algorithm's ability to determine the leakage point of in an air conditioning conditioner compressor. The location of the leakage point was is presented as a coordinated point. The results demonstrated that the leakage point during observed during the process could can be accurately detected, The the estimation point had has an error less than 5% compared to that of the the real leakage point.

1. Introduction

The air conditioner compressor is a major component in air conditioners and refrigerators. Air conditioning conditioner compressor manufacturing has four main subprocesses: (trimming a metal chassis, installing electrical and mechanical components into a compressor, assembling the chassis assembly, and inspecting quality inspection). Air conditioning compressor was a major part in air conditioning and refrigerator manufacturers. During the the compressor manufacturing process, incomplete welds process may cause very small leaks that are difficult to hard identify to be detected by manually human. Thus, before shipping the air conditioner conditioning compressor, out of the manufacture the assembled compressor will be is inspected to check the air conditioning compressor quality by for air leakage via detection and by searching for leakage points. Manual leakage detection by human causing has a high possibility of error, and therefore, therefore computer vision is implemented to reduce the costs of quality inspections compressors and increases the the accuracy, rapid speed, and reliability of the quality inspection process. A. Rosenfeld and J. L. Pfaltz [1] were proposed a connected connected-component labelling search for the connected pixels of object in a digital image [1]. W. Burger and M. J. Burge [2] were proposed a bounding box and centroid calculation of binary regions called blob analysis [2]. In this studywork, the connected connected-component labelling and blob analysis were chosen employed for detection; the proposed. The inspection method can be

applied to other closed tank products that where leakage detection and measurement is required.

2. Air conditioner Conditioning Compressor Inspection Test Ssetup

Insert Figure 1 here

Insert figure 1 here
In figure Figure: 1 presents a schematic diagram of the air conditioning compressor inspection test setup is presented. A The compressor is filled with is compressed air with under a pressure of 5 bars from the air pump. And Then, the compressor is submerged into the water in a transparent glass tank, and its position is fixed fix the test compressor at the middle position of the glass tank. Sequential images are taken captured by using a video webcam (OKER HD model 386). A computer with the an image processing algorithm was used to record and shows the inspection result in on a live video.

In this paper, we propose a new method to detect leakage and search leakage point is to improve the accuracy, fast and precise inspection process, better than human inspection. If compressed air in a compressor so that leakage

Comment [A1]: I have revised your title to improve clarity; I've discarded parts from the title that were not required here.

Comment [A2]: Note that I have used British English as required by the journal.

Comment [A3]: I have applied the template recommended by the target journal. All signposts from the template have been highlighted in yellow. Please remember to add the relevant information here.

Comment [A4]: I have added some background to ease the reader into the study.

Comment [A5]: I understand that this is the objective of your study.

Comment [A6]: Note that this term is generally referred to as "Air conditioner compressor"

Comment [A7]: Your paper does not provide a information on how these aspects were checked for

Comment [A8]: This line is unnecessary in the abstract and therefore, I have discarded it.

Comment [A9]: Did you mean "in the form of coordinates"?

Comment [A10]: How did you find the real leakage point?

Comment [A11]: The introduction provides of two references as background literature. This is insufficient to cover all aspects of the research I recommend that more studies be reviewed.

Comment [A20]: This is the first time you've mentioned this term. Please elaborate.

Comment [A12]: I have moved this sentence here to provide a better start to the text. Also, I'm

Comment [A13]: I recommend adding some more information about compressors and their

Formatted: Font: 10 pt, Italic, English (U.K)

Comment [A14]: What are incomplete welds? Did you mean incorrect welds?

Comment [A15]: Consider providing some details regarding leak size.

Comment [A21]: I have moved sections here to improve flow and clarity.

Comment [A22]: I could not comment on the figures; consider providing figures for the review.

Comment [A23]: I recommend using Pa as the unit here.

Comment [A24]: Why is it positioned at the centre?

Comment [A16]: In comparison to what? Are you referring to the manual process? You have no

Comment [A17]: Please include the reference without the reference details, it is difficult to verify

Comment [A25]: Consider revising this to "on real-time video".

Comment [A18]: There are other image processing techniques that could have been

Comment [A19]: For detection of leakage or the leakage point?

Formatted: Normal, Centered

was occurred. Air bubbles escaped from leakage point and float over to surface the water due to air pressure within a compressor.

In Further, to improve the visibility of air bubbles, a compressor inspection test setup, the a light source was installed above the compressor, and black curtains were used to so that air bubbles obviously are seen in white color. prevent external light noise. All curtain scenes are black to prevent external light noise [3], as shown Fig. 1.

Insert figure 1 here

In figure. 1, a schematic diagram of the air conditioning compressor inspection test setup is presented. A compressor is compressed air with under pressure of 5 bars from the air pump. And then submerge into the water transparent glass tank and fix the test compressor at middle position of the glass tank. Sequential images are taken by a video webcam (OKER HD model 386). A computer with the image processing algorithm was used to record and shows the inspection result in live video.

3. Image Processing Algorithm

The image sequences acquired from a the video camera is are stored in bitmap files. these files are and they were processed before the initial image processing to detect leakage by using connected component labelling technique and search leakage point by blob analysis to detect leakage and search the leakage point, respectively technique.

3.1. 3.1 Connected-Component Labelling Technique

Connected-Connected-component labelling is an image processing technique used to that is used to detect a connected region in binary digital images [4,5]. Connectivity is determined by the medium; image graphs, for example, can be 4four-connected or 8eight-connected [2].

3.1.3.2. 3.2 Blob Analysis Technique

Blob analysis is an image processing technique used to detect and measure blobs in images, as and make selected measurements of those blobs shown in Fig. 2. The cCenter of mass (or center of gravity-or/centroid) of a blob (x_c, y_c) is is calculated as by

$$y_c = \frac{1}{N} \sum_{i=1}^N y_i$$

$$x_c = \frac{\sum_{i=1}^N x_i}{N}, y_c = \frac{\sum_{i=1}^N y_i}{N} \quad (1)$$

where N is the number of pixels in the BLOB-blob and x_i and y_i are the x and y coordinates of the N pixels, respectively.

The bBounding box of a blob is the minimum rectangle which-that contains the blob. It-it is defined by going through all pixels for a blob and finding the four pixels with

the minimum x-value, maximum x-value, minimum y-value, and maximum y-value, respectively. From these values, the width of the bounding box is given as $x_{\max} - x_{\min}$ and the height as $y_{\max} - y_{\min}$. A bounding box can be used as the region of interest. The cCenter of the bounding box is calculated as

$$x_{bb} = x_{\min} + \frac{x_{\max} - x_{\min}}{2} = x_{\min} + \frac{x_{\max} - x_{\min}}{2} = \frac{x_{\min} + x_{\max}}{2} \quad (2)$$

$$y_{bb} = y_{\min} + \frac{y_{\max} - y_{\min}}{2} = y_{\min} + \frac{y_{\max} - y_{\min}}{2} = \frac{y_{\min} + y_{\max}}{2} \quad (3)$$

Insert Figure 2 here

Insert Figure 2 here

Generally In general, the proposed algorithm can be summarized as follows:

1. Initialize the threshold for white pixel detection and number of initial frames.
2. Colour images are acquired from a video camera are converted to binary images to separate the interest interest objects from a-the background. Binary images are filtered a-for noise by-using a median filter.
3. Use-The connected component labelling technique (8-connectivity) is used to detect a group of white pixels which-that is-are the air bubbles of interest. We-We implement the two-pass algorithm that iterates through binary data in an image.
- 3.4. Use-Blob analysis technique is used to detect blobs in an-the image, and we will get a centroid of blob and value of bounding box are obtained.
- 4-5. Compare the y_c of a-the blob with the previous frame and add a make a marker at this blob if y_c has a value greater than a-the previous frame. Display the result.
- 5-6. Check for the end frame.

The above procedure can also be described by the flowchart shown in Fig. 3.

Insert Figure 3 here

Insert Figure 3

Comment [A26]: I have discarded this text as revised first paragraph now details the same information.

Comment [A27]: What type of black curtains. Please provide details as this is necessary to replicate your study. Also, provide further details on the dimensions of the glass tank and the model of the compressor.

Comment [A31]: Note that equations should be included as figures. Please insert equations using an equation editor.

Comment [A28]: You're using connected component labelling, which requires binary images. You have not mentioned how you're converting your images to binary images anywhere.

Comment [A29]: I'm not sure what you mean "medium" here. Please consider clarifying.

Comment [A32]: Please consider clarifying what you mean by "that iterates through binary data".

Comment [A30]: I think it is better to refer to this as "centroid".

4. Experimental Result

Figure 3 shows a the colour image captured from the a-video camera and a-the pre-processed image. The experiments were performed using a-computer programming compatible-a-with-laptop with CPU Intel^(R) core^(TM) 2 Duo P7350. The original image size is-was 800 × 600 pixels.

Insert Figure 4 here

Insert Figure 4

Figures 5(a)–5(c) shows the red rectangle marker of the leakage point after processing in difference-different frames in image sequences to detect the first point to search by the connected component labelling technique and blob analysis technique, respectively.

Insert Figure 5 here

Insert Figure 5

5. Conclusion

A new inspection method to detect air leakage area and to search for the leakage point in air conditioner compressors with high accuracy, fastspeed, and reliable-reliability-inspection-process, was proposed. The method can be used to detect air bubbles that escape from an air conditioner conditioning compressor. A simple image processing algorithm consists of connected component labeling technique and blob analysis technique. The results demonstrated that the proposed method can identify the-air leakage in an air conditionereconditioning compressor effectively within-with an accuracy of 95%. The proposed method provides benefits-advantages for industrial application-such as cost reduction, reliability, and improvement of the manufacturing process and-and value treatment-maintenance of products.

6. Acknowledgments

Acknowledgements should be placed after the conclusion and before the references section. This is where reference to any grant numbers or supporting bodies should be included. The funding information should also be entered into the first submission step on Manuscript Central which collects Fundref information [4].

Please note that the IET does not include author biographies in published papers.

7. References

An average research paper should reference between 20 and 30 works, the bulk of which should be recently published (i.e. within the last five years) leading-edge articles in the field, preferably from top journals or

conferences. You should compare your own findings to this recent research and demonstrate how your work improves on it in order to demonstrate that your work shows a significant advance over the state of the art – a pre-requisite for publication in IET Research Journals.

Please note that tables, figures and equations should not appear in the middle of the references. If this happens white space will be introduced to avoid items appearing in the references.

7.1. Referencing Style

You should number your references sequentially throughout the text, and each reference should be individually numbered and enclosed in square brackets (e.g. [1]).

Please ensure that all references in the Reference list are cited in the text and vice versa. Failure to do so may cause delays in the production of your article.

Please also ensure that you provide as much information as possible to allow the reader to locate the article concerned. This is particularly important for articles appearing in conferences, workshops and books that may not appear in journal databases.

Do not include references for papers that have been submitted and not accepted for publication. Papers that have been accepted for publication are allowed as long as all information is provided.

Please provide all author name(s) and initials, title of the paper, date published, title of the journal or book, volume number, editors (if any), and finally the page range. For books and conferences, the town of publication and publisher (in parentheses) should also be given.

If the number of authors on a reference is greater than three please list the first three authors followed by *et al.* The reference list should be uninterrupted by figures, tables or equations.

Example References

7.2. Websites

[1] ‘Author Guide - IET Research Journals’, <http://digital-library.theiet.org/journals/author-guide>, accessed 27 November 2014

[2] ‘Research journal length policy’, http://digital-library.theiet.org/files/research_journals_length_policy.pdf, accessed 27 November 2014

7.3. Patent

[3] ‘ORCID: Connecting research and researchers’, <http://orcid.org/>, accessed 3 December 2014

[4] ‘Fundref’, <http://www.crossref.org/fundref/>, accessed 4 December 2014

7.4. Journal articles

Comment [A33]: The results are poorly presented. See my comments below.

Comment [A34]: I suggest that you draw a comparison between the manual methods, the methods for image detection, and your method on parameters such as speed, feasibility, reliability, and accuracy.

Comment [A35]: These lines are very convoluted and do not bring out your intended meaning clearly. Please clarify further so that I can provide a suitable suggestion.

Comment [A36]: This is your only paragraph in the results section. There is no comparison drawn in the paper only talks about detecting the bubbles and does not use any other parameters to evaluate the proposed algorithm.

Comment [A37]: The conclusion is insufficient in that it only talks about what has been stated previously. It does not provide limitations, future scope, or issues identified in this study.

Comment [A38]: None of these things were verified in your study. These parameters were not even measured.

Comment [A39]: There are other methods that have better accuracy but other limitations. Please consider conducting more thorough literature research and providing comparisons for the same.

Table 2 Example of large table

Column Heading 1	Column Heading 2	Column Heading 3	Column Heading 4
Result 1	123	123	123
Result 2	123	123	123
Result 3	123	123	123
Result 4	123	123	123
Result 5	123	123	123
Result 6	123	123	123
Result 7	123	123	123
Result 8	123	123	123

[5] Smith, T., Jones, M.: 'The title of the paper', *IET Syst. Biol.*, 2007, 1, (2), pp. 1–7

[6] Borwn, L., Thomas, H., James, C., et al.: 'The title of the paper', *IET Communications*, 2012, 6, (5), pp 125-138

7.5. Conference Paper

[7] Jones, L., Brown, D.: 'The title of the conference paper', *Proc. Int. Conf. Systems Biology*, Stockholm, Sweden, May 2006, pp. 1–7

7.6. Book, book chapter and manual

[8] Hodges, A., Smith, N.: 'The title of the book chapter', in Brown, S. (Ed.): 'Handbook of Systems Biology' (IEE Press, 2004, 1st edn.), pp. 1–7

[9] Harrison, E.A., and Abbott, C.: 'The title of the book' (XYZ Press, 2005, 2nd edn. 2006)

7.7. Report

[10] IET., 'Report Title' (Publisher, 2013), pp. 1-5

[11] Brown, F.: 'The title of the patent (if available)', *British Patent* 123456, July 2004

[12] Smith, D., Hodges, J.: *British Patent Application* 98765, 1925

7.8. Thesis

[13] Abbott, N.L.: 'The title of the thesis', PhD thesis, XYZ University, 2005

7.9. Standard

[14] BS1234: 'The title of the standard', 2006

8. Appendices

Additional material, e.g. mathematical derivations, tables and figures larger than half a page that may interrupt the flow of your paper's argument should form a separate Appendix section (see Table 2). Do not, however, use appendices to lengthen your article unnecessarily as this section is included in the word count. If the material can be found in another work, cite this work rather than reproduce it. The appendix section should be in double column format, and come after the references.